

item	description	specs	how many
16-Point unit	FMA-TM1116		9
AC Servo Motor	Type: USAREM-07CSL2KB S/N: BB0091059900001	700W, 5.7A, 200V 3000 r/min. cont.	1
Air Valve	501E1	DC 24V	3
Air Valve	VA500AE1 -51W	DC 24V -100~OKPa	1
Area Sensors	NA2-12P& 12D	12~24VDC	1 of each
Area Sensors	NA2-20D & 20P	12~24VDC	1 of each
Brake/Switch	A200-D90 (A100-D45)	AC200/220V (AC100/110V)	8
Branch Unit	FMA-TF4020-MB		5
Branch Unit	FMA-TF4120		2
CKD Parect Interface		AC Output 15V	1
Cosel	Power Supply P/N K15A-5	5V 3A	1
Cosel	Power Supply P/N K10A-5	5V 2A	1
Eliminostat-10	Complete set front and rear static bars. with air hook up.	AT-10 #590805050 SAT-10	1
FCN connector	FMA-TM1132-MB	32-point input unit. for Mitsubishi	2

item	description	specs	how many
Fuji electric	3 phase 2 poles Ring Blower	output: 550/850W Amps: 3.1/3.7/3.6	1
GTR electric induction motor	3 phase 4 poles MFG: 11240932A	Volts: 200/200/220 RPM:	1
GTR electric induction motor	3 phase 4 poles MFG: 11290467A	Volts: 200/200/220 RPM:	1
Hypoid Motor	Type: HMTA040-35H200B 3 phase-0.4kW-4P	Ratio: 1:200, 7.5/9/9 r/Min.	1
Induction electric geared motor	S/N: GFMN-15-5-T90 MFG: 11233209A	Ratio: 1:5 90W 200V cont.	1
Key Switch	P/N AR22JR-2A Serial: 41-10896	250V 600A	1
Koganei	Small Low Pressure Air Regulator.	ADJ. Range 0.02~0.5MPa	3
Lineard Motor	LM2B10SC-1 Electric Motor for X Axis	200V 0.18A Max. Thrust 20Ka	2
Lineard Motor	LM2B10SC-1 Electric Motor for Y Axis	200V 0.18A Max. Thrust 20Ka	1
Matsushita Circuit Protector	C11	AC220V 1A, 2A	1 of each
Matsushita Circuit Protector	C11D	DC48V 10A, 5A	1of each
Matsushita Circuit Protector	CP-C : C21,C20	AC220V 3A.5A.10A	1 of each
Matsushita circuit protector	Model: CP-C BAC201505	AC 220V IC 2.5kA 5A	2
Miki Pulley Electric motor	3 phase induction motor Serial: 81071550Y 065	Hz: 50/60/60 Rpm:	1

item	description	specs	how many
Mikipulley Power Supply	Model: BEJ-10 MFG: 11S2035	Input: AC 200V Output: DC 24V 2A	1
Mitsubishi	Inverter Model: FR-E520-0. 1K	Power: 0.1KW Inout: 1.5A 3PH	1
MITSUBISHI	A1S61PN	POWER SUPPLY MODULE 100	1
MITSUBISHI	A1SJ71QC24N	SERIAL COMM MOD. 232X1.	2
MITSUBISHI	A1SX42-S2	INPUT MODULE DC SINC 64	3
MITSUBISHI	A1SY42	OUTPUT MODULE 64POINT	3
MITSUBISHI	Q2AS-CPU-S1	CPU 60KSTEP 1024I/O	1
Mitsubishi FREQROL-E500 Inverter	model FR-E520-0.4k Serial: voz2vt240	power; 0.4kw	4
Mitsubishi Magnetic Contactor	S-N21	200V 50Hz 200-220V 60Hz	2
Mitsubishi Magnetic Contactor	S-N10	200V 50Hz 200-220V 60Hz	8
Mitsubishi no-fuse breakers	Model: NF30-KC 3 pole breakers	AC220V 20A 50 -60Hz Ui 500VAC	9 total
Mitsubishi programable contro.	Model: FX2n-128MT Serial: OZ4630	AC85~264V 50/60Hz 100VA	1
MKK DC FAN	MDF8015P24M	DC24V 0.1A	3
NAiS contacts	AY34002 RT3SP1-24V	AOZ102 24V	5

item	description	specs	how many
National Induction motor	THREE PHASE 4 Pole Model # EM-FBH	Hertz 50 60 60	1
Omron	APR-S Phase Reversal Relav	Voltage: 200/220VAC	1
Omron	Contactora Model: 13YOYA	250V 5A 24VDC	2
OMRON CONTACTS	G6B-4BND	5A 250VAC 5A 30VDC	10
OMRON Contacts	LY2N-D2 24VDC	10A 110VAC 1/2HP120VAC	15
Omron Power Supply	S82F-3024	DC Output 24V 14A	1
Omron- Limit Switch	ROLLER PLUNGER SWITCH	DC-12 0.5A/30V	1
Orion dry-pump	Model: CBX15/KRX3 Serial: 120006-1		2
Orion dry-pump	Model: CBX40/KRX6 Serial:110003-1		2
ORIX ac fan	model; mu1025S-41 Impedance protected ball	AC200V 200/200V	1
Orix AC Fan	Model: MRS16-DUL Thermally Protected	50 Hz 200V 0.24A 60 Hz 200V 0.24A	2
Patlite Signal Phone	Model: BM-202	Volt: 24V AC/DC Watt: 0.4W	1
Power Component	PMC-LUT-271	AC 100V 50/60Hz	1
Power supply	Omron S82J-15024E	Input: AC100 -120/200-240V	1

item	description	specs	how many
Pro-Face Digital Graphic Panel	P/N: GP270-LG11-24V S/N: 29510260160	DC 24V 12W	2
Serial transmission block	FMC-F201 DC24V With 11 F15T1	11Pcs. F15T1 DC24V	1 Block
SMC solenoid valves	vt317v	press. -101.2k~0.1mpa	5
SMC- Solenoid Valve	VT317	Press. 0~0.9MPa	1
SMC- Solenoid Valve	VT307-5GS-01-F	Press. 0~0.9MPa	2
speed controller(oriental motor)	MSP302N	model: MSP302N Serial numbers:	3
Super Line Induction Motor	3 phase 4 poles Type: SF-JR	Hz: 50/60/60 Rating: cont.	1
Super Line Induction Motor	3 phase 4 poles Type: SF-JR	Hz: 50/60/60 r/Min.	1
Super Vexta	5-Phase Driver Model: UDK5114N	AC 100V AC 115V	3
Terminal Block	PCN-1T20	125V/1A. AWG22 -16. 125V/1A.	4
Terminal Block	PCN-1T34	125V/1A. AWG22 -16. 125V/1A.	4
Terminal Block	PCN-1T40	125V/1A. AWG22 -16. 125V/1A.	8
Terminal Blocks	600V	We have a sorted selection of	7Pcs.
TOKIN- Noise Filter	GE-2050	AC. DC 250V. 5A TV. AC 1500V	2